



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

5MP 4.5Inch IP PTZ High Speed Dome Camera with wiper, Low temperature, P6SLite APP, 36X Optical Zoom Lens, P2P, Waterproof IP66.



Model: RP-H86-5MP-36X

Key features:

High performance chip (1/3" CMOS 5MP Hi3516E+Sony335).

5MP PTZ High Speed Dome IP Camera.

36X Optical Zoom Lens (4.5-162mm).

Efficient Resolution: 2592x1944@20fps/2592x1520@15fps.

Rotation Range (Pan: 0°~360°, Tilt: 0°~93°).

Rotation Speed (Pan: 0~200°/s, Tilt: 0~100°/s).

Auto Flip: Horizontal 180°, Vertical 93°.

APP Name: P6SLite

Support P2P function, H.265.

4.5" Total Metal Body Construction, IP66.

6PCS Array 42Mil IR LED+3PCS Laser LED, IR range up to 150M.

ONVIF, Compatible with HIKVISION, DAHUA, Raysharp, TVT, AEVISION NVR etc.

Intelligent IR illumination & power consumption is variable, dependant the zoom factor.

Product Advantages:

Offer 2-years product warranties.

Logistics convenient.

OEM/ODM.

CCC/CE/FCC Certified.

Strict product quality control.

Efficiently working with almost Hybrid DVR.

Lower price.

6-8 working day per order.

Product applications:



SHENZHEN RISE ELECTRONIC CO., LTD.

Website: <http://www.ideacamera.com> Email: cctv@ideacamera.com

Global Sources Homepage Address: <http://www.globalsources.com/ideacamera.co>

This is the best product of safety field. It and hard disk video recorders、cable、power supply、display、etc. Constitute a complete security system. Tts application is more extensive. Such as homes、factories、highways、office building、garden、community, or a large public places, etc.

Camera	
Sensor	1/3" CMOS 5MP Hi3516E+Sony335
Output pixel	2592x1944@20fps 2592x1520@15fps
Lens	36X f=4.5mm~162mm
BLC	Support
AGC	Auto/Manual
WB	Indoor/Outdoor/Auto/Manual
DNR	2DNR, 3DNR
WDR	DWDR
S/N Ratio	≥50dB
Dome	
Communications Protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, HTTPS, P2P
Software Control	IE, EasyVMS, P2P(P6SLite)
Mobile View(optional)	Android, iPhone
Rotation range	Pan:0~360°, Tilt:0~93°
Rotation speed	Pan:0~200°/s, Tilt:0~100°/s
Auto Flip	Horizontal 180°, Vertical 93°
Preset Points	220pcs presets (dwell time 01-60s interval available)
A-B scan	User programmable (scan speed 1-64 levels setting available)
Guard Tours	3 groups (Max.16 points, dwell time user selectable)
video compression	H.265/M-JPEG
Operating temperature	-40°C~+60°C
Operation menu	English
Power	DC 12V 4A
Consumption	≤25W
Related validation	IP66
IR Parameters	
Auto Control IR LED	PWM
LEDs	6PCS Array 42Mil IR LED+3PCS Laser LED
IR distance	Up to 150 meters